FR

GANTS DE PROTECTION CHIMIQUE EN NITRILE FLOQUÉ

Protection des mains – Gants de protection contre les risques chimiques

NGG6206

Née pour Protéger

Protection des mains

CE

EN 388
EN ISO 21420
EN ISO 374- 1
EN ISO 374- 5







Désignation :
NGG6206
Type d'EPI :
Protection des mains – Gants de protection contre les risques chimiques
Catégorie EPI : III
Description :
Les gants NGG6206 sont des gants de protection chimique en nitrile floqué, conçus pour protéger les mains contre une large gamme de produits chimiques et les micro-organismes.
Leur doublure floquée blanche améliore le confort, facilite l'enfilage et absorbe la transpiration lors d'un port prolongé.
Matériaux :
– Matériau extérieur : Nitrile
– Doublure intérieure : Flocage coton
– Finition : Surface texturée antidérapante
Caractéristiques :
- Longueur : ≈ 33 cm
- Épaisseur : ≈ 15 mil
- Manchette : Droite
- Bonne résistance aux produits chimiques et détergents

Performances mécaniques (EN 388) :
Abrasion : 3
Coupure (lame) : 1
Déchirure : 0
Perforation : 1
Coupure TDM : X
Protection chimique – EN ISO 374-1 (Type A)
Protection certifiée contre au moins les produits suivants :
- J – n-Heptane
- K – Hydroxyde de sodium 40 %
- L – Acide sulfurique 96 %
- O – Hydroxyde d'ammonium 25 %
- P – Peroxyde d'hydrogène 30 %
- T – Formaldéhyde 37 %

Protection biologique
- EN ISO 374-5:2016 :
  - Protection contre bactéries et champignons : PASS
  - Protection contre virus : non testée

Normes & Conformité :
EN ISO 21420:2020
EN 388:2016 + A1:2018
EN ISO 374-1:2016 + A1:2018 – Type A
EN ISO 374-5:2016
Conforme au Règlement (UE) 2016/425
Marquage CE
Tailles : 7 – 8 – 9 – 10 – 11
Couleurs :
Extérieur : vert
Intérieur : blanc
Domaines d'application :
– Industrie chimique / Nettoyage industriel / Maintenance et traitement de surfaces / Laboratoires / Manipulation de produits chimiques/ Collectivités et services techniques
Atouts produit :
– Protection chimique Type A / Bonne résistance mécanique pour un gant chimique / Doublure floquée pour plus de confort / Surface antidérapante / Adapté à un usage prolongé
Conditionnement :
– 1 paire / sachet individuel
– 12 paires / sachet
– 120 paires / carton

TANSAN

EN

FLOCK-LINED NITRILE CHEMICAL PROTECTIVE GLOVES

Hand Protection – Chemical protective gloves

NGG6206

Born to Protect.

Hand Protection

CE

EN 388
EN ISO 21420
EN ISO 374- 1
EN ISO 374- 5







Product Name :
NGG6206
PPE Type:
Hand Protection – Chemical protective gloves
PPE Category: III
Description:
NGG6206 gloves are flock-lined nitrile chemical protective gloves designed to protect hands against a wide range of chemical hazards and micro-organisms. The white cotton flock lining improves comfort, absorbs perspiration, and makes donning easier during prolonged use.
Materials :
– Outer material: Nitrile
– Inner lining: Cotton flock
– Finish: Textured anti-slip surface
Features :
- Length: approx. 33 cm
- Thickness: approx. 15 mil
- Cuff: Straight
- Good resistance to chemicals and detergents

Mechanical Performance (EN 388) :
Abrasion resistance: 3
Blade cut resistance: 1
Tear resistance: 0
Puncture resistance: 1
Cut resistance (TDM): X
Chemical Protection – EN ISO 374-1 (Type A)
Certified protection against at least the following chemicals:
- J – n-Heptane
- K – Sodium hydroxide 40 %
- L – Sulphuric acid 96 %
- O – Ammonium hydroxide 25 %
- P – Hydrogen peroxide 30 %
- T – Formaldehyde 37 %

Biological Protection :
- EN ISO 374-5:2016
  - Protection against bacteria and fungi: PASS
  - Protection against viruses: Not tested

Standards & Compliance
EN ISO 21420:2020
EN 388:2016 + A1:2018
EN ISO 374-1:2016 + A1:2018 – Type A
EN ISO 374-5:2016
Compliant with Regulation (EU) 2016/425
CE marking
Sizes :
7 – 8 – 9 – 10 – 11
Colours :
Outer: Green
Inner: White
Applications :
Chemical industry / Industrial cleaning / Maintenance and surface treatment / Laboratories / Chemical handling / Public utilities and services
Key Benefits :
Type A chemical protection / Good mechanical resistance for chemical gloves / Comfortable flock lining / Anti-slip grip / Suitable for prolonged use
Packaging :
– 1 pair / individual polybag
– 12 pairs / polybag
– 120 pairs / carton

TANSAN